

Light efficiency:


11 Lumen/Watt

Light quality:

CRI: 0.0

Color temperature:

0 K



Product name:

Chorus Line16

Test:


Zoom Out Full On

Date:


7/20/2017

Output: 5713 lm Power consumption: 510 W Peak: 14239 cd


Spectral distribution




Color coordinates



Zoom color point




CRI R values



Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color divition from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
0 K	0.0	0.0	0.0	0.0	0.0	0.245	0.187	0.207	0.236	n/a

Beam details



Beam angels

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%
37.8°	54.4°	67.1°

Beam intensities

Peak intensity	Int. ratio in 120° cone	Int. ratio in 90° cone
14239 cd	97.0%	96.0%

Power

Power	Power factor	Power frequency
510 W	1.0	0 Hz

Nominal voltage	Voltage	Current
230 V	115 V	4.42 A

Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
14239lx	3560lx	1582lx	890lx	570lx	396lx	291lx	222lx	176lx	142lx	118lx	99lx	84lx	73lx	63lx	56lx	49lx	44lx	39lx	36lx
1322.8fcd	330.7fcd	147fcd	82.7fcd	52.9fcd	36.7fcd	27fcd	20.7fcd	16.3fcd	13.2fcd	10.9fcd	9.2fcd	7.8fcd	6.7fcd	5.9fcd	5.2fcd	4.6fcd	4.1fcd	3.7fcd	3.3fcd