KEY FEATURES
Portable and compact fully featured lighting console
Adjustable 15.6" Full HD multi touch screen, 2x external 4K Touch Displays
64 Universe integrated processing
10 Playbacks, 8 Encoders, Keypad and internal 3.5" touchscreen
Network,DMX, Timecode and Midi Connectivity

SPECIFICATIONS
SURFACE
10 x 60 mm playback faders, each with 4 x function-assignable buttons
8 x customizable multi-function keys
Playback Select button
Master Go section with Go, Pause, Snap and Release
4 x digital rotary encoders with push function and status LED for fixture parameter control
4x screen mounted digital rotary encoders with push
3.5" RGB touchscreen for parameter groups, effect parameters, fanning and global timings
Grand master rotary fader and button
Blind/HighLight/Last/Next buttons
Full numerical keypad and command keys

HARDWARE
8 x customizable multi-function keys
Playback Select button
Master Go section with Go, Pause, Snap and Release
4 x digital rotary encoders with push function and status LED for fixture parameter control
4x screen mounted digital rotary encoders with push
3.5" RGB touchscreen for parameter groups, effect parameters, fanning and global timings
Grand master rotary fader and button
Blind/HighLight/Last/Next buttons
Full numerical keypad and command keys
Industrial 15.6" TFT 16:9 touchscreen (1920x1080px)
250 GB NVMe M.2 storage drive
Industrial motherboard with Intel i5 Hexa-Core CPU

HARDWARE
Quiet thermal design using advanced copper heat pipe coolers
16 GB DDR4 RAM
Integrated graphics processor
Windows 10 IoT Embedded Operating System
OS installation by USB 3.0 storage device
Supports Windows USB touchscreens

CONNECTIONS
250 GB NVMe M.2 storage drive
Industrial motherboard with Intel i5 Hexa-Core CPU
Quiet thermal design using advanced copper heat pipe coolers
16 GB DDR4 RAM
Integrated graphics processor
Windows 10 IoT Embedded Operating System
OS installation by USB 3.0 storage device
Supports Windows USB touchscreens
4 x DMX / RDM Universe In/Out: 5-pin locking XLR
External Display: 2x DisplayPort (up to 4k)
Network: 2x Gigabit for Art-Net, sACN and ONYX X-Net
Storage and Peripherals: 4x USB 3.0, 1x USB 2.0
Audio Out, Mic In: 2x 3.5mm Jack
MIDI in/out/thru (MIDI Showcontrol, MIDI notes, MIDI Timecode): 5pin DIN
SMPTE Timecode In/Out: 3-pin XLR
12 VDC power supply input: 4-pin XLR
Desk lamp: XLR 12V
USB In: USB 2.0 B

PHYSICAL
Length: 300 mm (11.9 in.)
Width: 540 mm (21.3 in.)
Height: 121 mm (4.8 in.)
Weight: 9 kg (19.8 lbs.)

ELECTRICAL
AC mains power to 12VDC external PSU (included):
100-240V nominal, 50/60 Hz
Maximum current: 3A
12VDC output: 11A, 132W max.

ORDERING
INCLUDED ITEMS
RGB LED desk lamp, angular XLR connector, 13"
Dust Cover
Obsidian USB Cable
External PSU (12V 11A)
1.5 m power cable, 3-pin IEC

SKU
US #: NX2984
EU #: 1330000047

300 mm
(11.9 in.)

540 mm
(21.3 in.)

121 mm
(4.8 in.)