

Product Overview

FUZE SPOT	FUZE PROFILE	FUZE WASH FR	FUZE PROFILE CW	FUZE SFX
SOURCE <ul style="list-style-type: none"> 305W 6,500K RGBMA 92 CRI LED engine 30,000 hour average LED life* 	SOURCE <ul style="list-style-type: none"> 305W 6,500K RGBMA 92 CRI LED engine 30,000 hour average LED life* 	SOURCE <ul style="list-style-type: none"> 480W 6,500K RGBMA 92 CRI LED engine 30,000 hour average LED life* 	SOURCE <ul style="list-style-type: none"> 380W 6,000K 91 CRI white LED Engine 30,000 hour average LED life* 	SOURCE <ul style="list-style-type: none"> 300W LED 6,800k 70 CRI white LED engine CMY variable color mix
PHOTOMETRIC DATA <ul style="list-style-type: none"> 10,000+ total lumen output 	PHOTOMETRIC DATA <ul style="list-style-type: none"> 10,000+ total lumen output 	PHOTOMETRIC DATA <ul style="list-style-type: none"> 14,000+ total lumen output 	PHOTOMETRIC DATA <ul style="list-style-type: none"> 11,000 total lumen output 	PHOTOMETRIC DATA <ul style="list-style-type: none"> 12,000+ total lumen output
EFFECTS <ul style="list-style-type: none"> 7° - 42° motorized zoom Variable frost filter 4 facet prism Motorized iris Variable 16-bit dimming curve modes 	EFFECTS <ul style="list-style-type: none"> 7° - 42° motorized zoom 4 rotating full blackout framing blades, +/- 45 index Variable frost filter 4 facet prism Motorized Iris 	EFFECTS <ul style="list-style-type: none"> 9° - 60° motorized zoom Variable frost filter 4 rotating full blackout framing blades, +/- 45 index Motorized iris Variable 16-bit dimming curve modes 	EFFECTS <ul style="list-style-type: none"> 9° - 43° motorized zoom 4 rotating full blackout framing blades, +/- 45 index Motorized iris Variable 16-bit dimming curve modes 	EFFECTS <ul style="list-style-type: none"> 4.5° - 38° motorized zoom Remote Focus Variable Frost Filter Dual Independent Prisms for layering Motorized Iris
GOBOS <ul style="list-style-type: none"> 2x 6 Rotating / indexing interchangeable glass gobos Animation wheel 	GOBOS <ul style="list-style-type: none"> 1x 6 rotating / indexing glass gobos, 1x 7 fixed glass Animation wheel 	GOBOS <ul style="list-style-type: none"> N/A 	GOBOS <ul style="list-style-type: none"> 1 Gobo Wheel 7 Rotating / Indexing Interchangeable Glass Gobos 	GOBOS <ul style="list-style-type: none"> Rotating Gobo Wheel with 8 Interchangeable Glass Gobos Fixed Gobo Wheel with 10 Gobos
CONTROL / CONNECTIONS <ul style="list-style-type: none"> 4 DMX channel modes (RGBMA 31 / 41) (CMY 29 / 37) 16-bit pan, tilt, and dimming control DMX Adjustable LED frequency DMX, RDM protocol support Locking 5pin XLR In/Out Locking power In/Out 	CONTROL / CONNECTIONS <ul style="list-style-type: none"> 4 DMX channel modes (RGBMA 38 / 59) (CMY 36 / 55) 16-bit pan, tilt, and dimming control DMX, RDM protocol support Locking 5pin XLR In/Out Locking power In/Out 	CONTROL / CONNECTIONS <ul style="list-style-type: none"> 4 DMX channel modes (RGBMA 29/47) (CMY 27/43) 16-bit pan, tilt, and dimming control DMX adjustable DMX frequency Locking RJ45 Ethernet (Artnet, sACN) in/out 	CONTROL / CONNECTIONS <ul style="list-style-type: none"> 2 DMX channel modes (26 / 40) 16-bit pan, tilt, and dimming control Motorized Focus DMX, RDM protocol support Locking 5pin XLR In/Out Locking power in/out 	CONTROL / CONNECTIONS <ul style="list-style-type: none"> 31 DMX channels 16-bit pan, tilt, and dimming control DMX, RDM, Art-NET, and sACN protocol support Elation's E-FLY™ internal wireless DMX transceiver Locking 5pin XLR In/Out Locking RJ45 Ethernet In/Out Locking power in/out
SIZE / WEIGHT <ul style="list-style-type: none"> LxWxH: 16.0" x 10.1 x 27.4" 407 x 256 x 698mm Weight: 46.3 lbs. (21kg) 	SIZE / WEIGHT <ul style="list-style-type: none"> LxWxH: 16.0" x 10.1" x 27.4" 407 x 256 x 698mm Weight: 55.1 lbs. (25kg) 	SIZE / WEIGHT <ul style="list-style-type: none"> LxWxH: 16.0" x 10.1 x 23.41" 407 x 256 x 595mm Weight: 55.1lbs (25kg) 	SIZE / WEIGHT <ul style="list-style-type: none"> LxWxH: 15.9" x 9.9" x 27.4" 408 x 252 x 698mm Weight: 51.4 lbs. (23.3kg) 	SIZE / WEIGHT <ul style="list-style-type: none"> LxWxH: 14.6" x 10.1" x 23.6" 370x 230 x 600mm Weight: 46.3 lbs. (19.3kg)

FUZE WASH Z350	FUZE WASH Z120	FUZE WASH 575	FUZE PAR Z60 IP	FUZE PAR Z120 IP	FUZE PAR Z175
SOURCE <ul style="list-style-type: none"> 350W RGBW COB LED 100,000 hour average LED life* 	SOURCE <ul style="list-style-type: none"> 120W RGBW COB LED 100,000 hour average LED life* 	SOURCE <ul style="list-style-type: none"> 350W 95CRI 6,800K CW / daylight COB LED 50,000 hour average LED life* 	SOURCE <ul style="list-style-type: none"> 60W RGBW COB LED 100,000 hour average LED life* 	SOURCE <ul style="list-style-type: none"> 120W RGBW COB LED 100,000 hour average LED life* 	SOURCE <ul style="list-style-type: none"> 175W RGBW COB LED 50,000 hour average LED life*
PHOTOMETRIC DATA (2m) <ul style="list-style-type: none"> 60,280 LUX 5,600 FC @ 6.6' (6°) 3,735 LUX 347 FC @ 6.6' (46°) 	PHOTOMETRIC DATA (3m) <ul style="list-style-type: none"> 10,640 LUX 988 FC @ 9.8' (7°) 692 LUX 64 FC @ 9.8' (55°) 	PHOTOMETRIC DATA (2m) <ul style="list-style-type: none"> 6,502 LUX 604 FC @ 6.6' (2m) (40° Full On) 	PHOTOMETRIC DATA (3m) <ul style="list-style-type: none"> 3,813 LUX 354 FC @ 9.8' (7°) 228 LUX 21 FC @ 9.8' (39°) 	PHOTOMETRIC DATA (3m) <ul style="list-style-type: none"> 9,112 LUX 847 FC @ 9.8' (7°) 428 LUX 40 FC @ 9.8' (55°) 	PHOTOMETRIC DATA (2m) <ul style="list-style-type: none"> 15,026 LUX 1396 FC @ 6.6 ft (8°) 3,481 LUX 323 FC @ 6.6 ft (35°)
EFFECTS <ul style="list-style-type: none"> RGBW Color Mixing 6° - 46° beam zoom range Electronic strobe, dimming & variable dimming curves 64 color presets and 14 unique color macros 	EFFECTS <ul style="list-style-type: none"> RGBW Color Mixing 7° - 55° Beam zoom range Electronic strobe, dimming & variable dimming curves 64 color presets and 14 unique color macros 	EFFECTS <ul style="list-style-type: none"> 11° - 40° motorized zoom Electronic strobe Variable dimming curve modes 	EFFECTS <ul style="list-style-type: none"> RGBW Color Mixing 7° - 39° Beam zoom range Electronic strobe, dimming and variable dimming curves 64 color presets and 14 unique color macros 	EFFECTS <ul style="list-style-type: none"> RGBW Color Mixing 7° - 55° beam zoom range Electronic strobe, dimming and variable dimming curves 64 color presets and 14 unique color macros 	EFFECTS <ul style="list-style-type: none"> 8° - 35° motorized zoom 64 color presets and color macro programs Electronic strobe 16-bit variable dimming curve modes
CONTROL / CONNECTIONS <ul style="list-style-type: none"> 4 DMX channel modes (19 total channels) 7 button control panel and LCD menu display Locking 3pin/5pin XLR DMX and Power in/out 	CONTROL / CONNECTIONS <ul style="list-style-type: none"> 4 DMX channel modes (19 total channels) 7 button control panel and LCD menu display Locking 3pin/5pin XLR DMX and Power in/out 	CONTROL / CONNECTIONS <ul style="list-style-type: none"> 2 DMX channel modes (11 total channels) 7 button control panel and LCD menu display Locking 5pin XLR In/Out Locking power In/Out 	CONTROL / CONNECTIONS <ul style="list-style-type: none"> 12 DMX channel modes (13 total channels) 4 button touch control panel & LCD menu display IP65 Locking 5pin XLR DMX and Power in/out 	CONTROL / CONNECTIONS <ul style="list-style-type: none"> 12 DMX channel modes (13 total channels) 4 button touch control panel & LCD menu display IP65 Locking 5pin XLR DMX and Power in/out 	CONTROL / CONNECTIONS <ul style="list-style-type: none"> 12 DMX channel modes (14 total channels) 4 button control panel and LCD menu display Locking 3/5pin XLR In/Out Locking power In/Out
SIZE / WEIGHT <ul style="list-style-type: none"> LxWxH: 16.3" x 11.6" x 22.7" 414 x 294 x 578mm Weight: 45 lbs. (20.4 kg) 	SIZE / WEIGHT <ul style="list-style-type: none"> LxWxH: 13.3" x 9.0" x 18.2" 338 x 229 x 466mm Weight: 22 lbs. (10 kg) 	SIZE / WEIGHT <ul style="list-style-type: none"> LxWxH: 3.3" x 9.0" x 18.33" 337.7 x 228.8 x 465.7mm Weight: 27.0 lbs. (12.2kg) 	SIZE / WEIGHT <ul style="list-style-type: none"> LxWxH: 10.0" x 9.9" x 11.1" 253 x 252 x 282mm Weight: 10 lbs. (4.5 kg) 	SIZE / WEIGHT <ul style="list-style-type: none"> LxWxH: 11.69" x 14.05" x 14.14" 283.7 x 356.8 x 359.2mm Weight: 19 lbs. (8.6 kg) 	SIZE / WEIGHT <ul style="list-style-type: none"> LxWxH: 18.2" x 16.2" x 17.0" 463 x 411 x 431mm Weight: 20.0 lbs. (9.07kg)



Elation Professional Europe

Junostraat 2 • 6468 EW Kerkrade • The Netherlands

www.elationlighting.eu

*Lamp/ LED Life may vary depending on several factors including but not limited to: Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control, and Dimming. Gobos & Colors. Specifications subject to change without notice.