

Product Overview

PROTEUS LUCIUS	PROTEUS MAXIMUS	PROTEUS HYBRID	PROTEUS SMARTY HYBRID	PROTEUS RAYZOR 760
SOURCE <ul style="list-style-type: none"> 580W 6,500K Bright White Hotspot LED Engine 30,000 Hour Average LED Life* 	SOURCE <ul style="list-style-type: none"> 950W 6,500K Bright White LED Engine 30,000 Hour Average LED Life* 	SOURCE <ul style="list-style-type: none"> Philips MSD 21R 470W 8,000K Lamp 1,000 Hour Average Lamp Life* 	SOURCE <ul style="list-style-type: none"> Philips™ MSD Platinum 200 Flex 280W Lamp Up To 6,000 Hour Lamp Life* 	SOURCE <ul style="list-style-type: none"> 7 60W Osram RGBW LEDs 28 2W White SparkLED™ 50,000 Hour Average LED Life*
PHOTOMETRIC DATA <ul style="list-style-type: none"> 31,000 Total Lumen Fixture Output CRI 71+ (85+ with HCRI Filter) 2.5:1 Hotspot Ratio 	PHOTOMETRIC DATA <ul style="list-style-type: none"> 50,000 Total Lumen Output CRI 70+ (82+ with HCRI Filter) 2:1 Hotspot Ratio 	PHOTOMETRIC DATA (15m) <ul style="list-style-type: none"> 80 CRI >23,000 Total Lumen Output 13,375 LUX 1,243 FC @ 49.2' (3.0° Spot) 	PHOTOMETRIC DATA (preliminary) <ul style="list-style-type: none"> Up to 11,000 Total Lumen Output 128,426 LUX @ 15m (Beam Mode) 	PHOTOMETRIC DATA <ul style="list-style-type: none"> Up to 8,000 Total Lumen Output
EFFECTS <ul style="list-style-type: none"> 5.5 - 55° Motorized Zoom 4 Rotating Full Blackout Framing Blades +/-50° Continuous Framing Indexing Full 360° Bi-Directional Animation Wheel 4-Facet and Linear Rotating Prisms 2 Variable Frost Filters (Light and Wash) Internal Color, Framing, Prism, and Frost Macros Motorized Iris with Variable Pulse Effects Variable 16-bit Dimming Curve Modes High Speed Electronic Shutter and Strobe DMX Controllable LED Refresh Rate 	EFFECTS <ul style="list-style-type: none"> 5.5 - 55° Motorized Zoom (Large 180mm Front Aperture) 4 Rotating Full Blackout Framing Blades +/-50° Continuous Framing Indexing Full 360° Bi-Directional Animation Wheel 4-Facet and Linear Rotating Prisms 2 Variable Frost Filters (Light and Wash) Internal Color, Framing, Prism, and Frost Macros Motorized Iris with Variable Pulse Effects Variable 16-bit Dimming Curve Modes High Speed Electronic Shutter and Strobe DMX Controllable LED Refresh Rate 	EFFECTS <ul style="list-style-type: none"> Motorized Zoom, 2° Beam to 38° Spot or 40° Wash Full 360° Bi-Directional Animation Wheel Rotating Prisms and Prism Macros Frost Filter Hybrid Wash Effect Motorized Focus and Auto-focus High Speed Mechanical Shutter and Strobe 	EFFECTS <ul style="list-style-type: none"> Beam, Spot, Wash Modes Motorized Zoom 1° - 18° Beam, 3° - 27° Spot, 5° - 33° Wash Full Frost Filter for Wash Effects 16-Facet and 5-Facet Linear Prisms CMY Color, Gobo, Prism Macros Motorized Focus with Auto-focus Feature High speed Shutter and Strobe 	EFFECTS <ul style="list-style-type: none"> 5° - 77° Beam to Wash Zoom Angle Linear Color Temperature Presets (2,700 - 8,000K) RGBW Color Mixing and Pixel Control White SparkLED™ Lens Effect Color Presets and Macros Electronic Strobe and Variable Dimming Curves 16-bit Dimming
COLOR <ul style="list-style-type: none"> CMY Color Mixing Linear CTO Color Correction 5 Dichroic Colors including High CRI Filter 	COLOR <ul style="list-style-type: none"> CMY Color Mixing Linear CTO Color Correction 6 Dichroic Colors including High CRI Filter and UV 	COLOR <ul style="list-style-type: none"> Full CMY Color Mixing and Linear CTO Color Correction 14 Dichroic Colors including CTB, CTO, and UV 	COLOR <ul style="list-style-type: none"> Full CMY Color Mixing System 13 Colors including Quad Color, CTO, CTB, and UV 	COLOR <ul style="list-style-type: none"> 7 RGBW LEDs 28 White SparkLED™
GOBOS <ul style="list-style-type: none"> 3 Gobo Wheels 6 Rotating Gobo (Wheel #1) 7 Rotating Gobos (Wheel #2) 7 Static Gobos (Wheel #3) 	GOBOS <ul style="list-style-type: none"> 2 Gobo Wheels 6 Rotating / Indexing Interchangeable Glass Gobos 7 Static Glass Gobos 	GOBOS <ul style="list-style-type: none"> 8 Interchangeable Rotating / Indexing Glass Gobos 14 Static-Stamped Metal Gobos 	GOBOS <ul style="list-style-type: none"> 2 Gobo Wheels 8 Rotating / indexing Interchangeable Glass Gobos 12 Static-Stamped Metal Gobos 	GOBOS <ul style="list-style-type: none"> N/A
CONTROL / CONNECTIONS <ul style="list-style-type: none"> 2 DMX Channel Modes 16-bit Pan, Tilt and Dimming Control Motorized Focus and Auto-Focus Presets DMX, RDM, Art-NET, sACN Protocol Support (6) Button Touch Control Panel Full Color 180° Reversible LCD Menu Display Hibernation Mode (Power Save) IP65 Locking 5pin XLR DMX In/Out, RJ45 Ethernet In/Out and Power In With Wired Digital Communication Network 	CONTROL / CONNECTIONS <ul style="list-style-type: none"> 2 DMX Channel Modes (37 / 61) 16-bit Pan, Tilt and Dimming Control Motorized Focus and Auto-Focus Presets DMX, RDM, Art-NET, sACN Protocol Support (6) Button Touch Control Panel Full Color 180° Reversible LCD Menu Display Hibernation Mode (Power Save) IP65 Locking 5pin XLR DMX In/Out, RJ45 Ethernet In/Out and Power In With Wired Digital Communication Network 	CONTROL / CONNECTIONS <ul style="list-style-type: none"> 3 DMX Channel Modes (24 / 26 / 37) 6 Button Touch Control Panel Full Color 180° Reversible LCD Menu Display 8 / 16 bit Resolution Adjustable Movement DMX, RDM, Art-NET and sACN Protocol Support Elation's E-FLY™ Internal Wireless DMX Transceiver IP65 Locking 5pin XLR DMX In/Out, RJ45 Ethernet In/Out and Power In 	CONTROL / CONNECTIONS <ul style="list-style-type: none"> 2 DMX Channel Modes (20 / 34) DMX, RDM, Art-NET and sACN Protocol Support (6) Button Touch Control Panel Full Color 180° Reversible LCD Menu Display IP65 Locking 5pin XLR DMX In/Out, RJ45 Ethernet In/Out and Power In 	CONTROL / CONNECTIONS <ul style="list-style-type: none"> 3 DMX Channel Modes 360° Continuous Pan and Tilt Movement DMX Adjustable Refresh Rate (900 - 25,000 Hz) (6) Button Touch Panel Full Color 180° Reversible LCD menu Display RDM Support IP65 Locking 5pin XLR DMX In/Out, RJ45 Ethernet In/Out and Power In
SIZE / WEIGHT <ul style="list-style-type: none"> Length: 17.5 in (445mm) Width: 19.6 in (499mm) Height: 28.1 in (715mm) Weight: 91.4 lbs. (41.5kg) 	SIZE / WEIGHT <ul style="list-style-type: none"> Length: 18.0 in (458mm) Width: 23.3 in (591mm) Height: 32.5 in (825mm) Weight: 117 lbs. (53kg) 	SIZE / WEIGHT <ul style="list-style-type: none"> Length: 17.5" (445mm) Width: 22.5" (572mm) Vertical Height: 31.5" (800mm) Weight: 84.0 lbs. (38 kg) 	SIZE / WEIGHT <ul style="list-style-type: none"> Length: 17.5 in (444.71mm) Width: 17.88 in (459mm) Height: 26.97 in (685mm) Weight: 78.26 lbs. (35.5kg) 	SIZE / WEIGHT <ul style="list-style-type: none"> Length: 367mm (14.5 in) Width: 295mm (11.6 in) Height: 442mm (17.4 in) Weight: 13kg (28.6 lbs.)
ELECTRICAL / THERMAL <ul style="list-style-type: none"> AC 100-240V 50/60Hz Max Power Consumption 880W 14°F to 113°F (-10°C to 45°C) 	ELECTRICAL / THERMAL <ul style="list-style-type: none"> AC 100-240V 50/60Hz Max Power Consumption 1,400W 14°F to 113°F (-10°C to 45°C) 	ELECTRICAL / THERMAL <ul style="list-style-type: none"> AC 100-240V - 50/60Hz Max Power Consumption 700W 14°F to 113°F (-10°C to 45°C) 	ELECTRICAL / THERMAL <ul style="list-style-type: none"> AC 100-240V 50/60Hz Max Power Consumption 500W 14°F to 113°F (-10°C to 45°C) 	ELECTRICAL / THERMAL <ul style="list-style-type: none"> AC 100-240V 50/60Hz Max Power Consumption 700W 14°F to 113°F (-10°C to 45°C)



PROTEUS



Elation Professional Europe
 Junostraat 2 • 6468 EW Kerkrade • The Netherlands
www.elationlighting.eu



PROTEUS

*Lamp/ LED Life may vary depending on several factors including but not limited to: Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control, and Dimming. Gobos & Colors. Specifications subject to change without notice.