



CHORUS LINE 8™



The CHORUS LINE 8™ is an 8 pixel bar wash luminaire featuring 40W 4-in-1 RGBW LEDs, motorized 4° to 40° zoom and 220° tilt movement, full pixel control, 2,700K - 7,000K adjustable linear color temperature, 64 color presets and 14 unique color macros, electronic strobe and 16-bit variable dimming curve modes, adjustable LED refresh rate frequency and gamma brightness for flicker free operation for TV and FILM, DMX, RDM, KlingNET and Art-NET protocol support, 5pin DMX, RJ45 ethernet, and Locking Power Cable in/out connections, 4 button LCD control panel display, dual quick-lock omega bracket rigging, and a multi-voltage universal auto switching power supply (110-240v).

FEATURES

8 Pixel Bar Wash Luminaire with 40W 4-in-1 RGBW LEDs

Motorized 4° to 40° Zoom and 220° Tilt Movement

RGBW Color Mixing and Full Pixel Control

2,700K - 7,000K Linear Color Temperature Range

64 Color Presets and 14 Unique Color Macros

Electronic Strobe, 16-bit Variable Dimming Curve Modes

Adjustable LED Refresh Rate Frequency

Adjustable LED GAMMA Brightness

Flicker Free Operation for TV and FILM

DMX, RDM, Kling-Net, Art-Net Protocol Support



SPECIFICATIONS

SOURCE

(8) 40W 4-in-1 RGBW LEDs
50,000 Hour Average LED Life*

*May vary depending on several factors including but not limited to:
Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control and Dimming.

PHOTOMETRIC DATA

3000+ Total Output Lumens
8,702 LUX 809 FC @16.4' (5m) (4° Min Zoom)
318 LUX 21 FC @16.4' (5m) (37° Max Zoom)

EFFECTS

Motorized 4° to 40° Zoom and 220° Tilt Movement
RGBW Color Mixing and Full Pixel Control
2,700K - 7000K Linear Color Temperature Range
64 Color Presets and 14 Unique Color Macros
Electronic Strobe, 16-bit Variable Dimming Curve Modes

COLOR

RGBW

CONTROL / CONNECTIONS

3 DMX Channel Modes (46 total channels)
DMX, RDM, Kling-Net, and Art-Net Protocol Support
Adjustable LED Refresh Rate (900-25,000Hz)
Adjustable LED Gamma Brightness (2.0, 2.2, 2.4, 2.8)
4 Button Touch Control Panel
180° Reversible LCD Menu Display
8/16-Bit Resolution Zoom and Tilt Movement
5pin DMX In/Out
RJ45 ethernet In/Out
Locking Power Cable In/Out

SIZE / WEIGHT

Length: 21.28" (540.5mm)
Width: 7.44" (189mm)
Vertical Height: 11.46" (291mm)
Weight: 25.0 lbs. (11.3 kg)

ELECTRICAL / THERMAL

AC 100-240V - 50/60Hz
359W Max Power Consumption
5°F to 113°F (-15°C to 45°C)
BTU/hr (+/- 10%) 1224.19

APPROVALS / RATINGS



INCLUDED ITEMS

Omega Brackets (x2)
Locking Power Cable

ORDERING INFORMATION

PRODUCT ORDER CODE	
CHO001	CHORUS LINE 8
OPTIONAL ACCESSORIES ORDER CODES	
DRCC18	6-Pack Road Case for Chorus Line 8
TRIGGER CLAMP	Heavy Duty Wrap Around Hook Style Clamp
AC5PDMX5PRO	5 ft. (1.5m) 5pin PRO DMX Cable
CAT6PRO5	5' (1.5m) CAT6 Ethernet Cable
NEU088	3' (1m) Power Locking Link Cable
	Additional cable lengths available

DIMENSIONS

