



SPECIFICATIONS

Pixel Pitch: 3.9mm

Physical Density: 65,536 (dots/m2)

LED Type: SMD Chip

LED Size: SMD 2121

Module Size: 250 x 250mm

Module Resolution: 64 x 64 pixels

Drive Mode: Constant Current Drive

Horizontal and Vertical View Angle: H:140° | V:120°

Scan Way: 1/16

Cabinet Size: 500 x 500mm

Cabinet Resolution: 128 x 128 pixels

Cabinet Weight: ≥18.7 lbs. (≥8.5 kg)

Cabinet Material: Die Cast Aluminum Alloy

Brightness: 1200 (cd/m2) (after calibration)

Gray Scale: 14bit

Refresh Rate: Variable Up To 3840Hz

Input Voltage: AC110V-220V, 50/60Hz

Cabinet Max Power Consumption: 135W

Cabinet Average Max Power Consumption: 50W

Protection Level: IP20

Environment: Indoors | -20° - 40° C | 10 - 90% RH

Life Span: ≥50,000 Hours



OPTIONAL ACCESSORIES

EVH120 - EVHD Series Rear Support Bracket (Install Version)

EVH254 - EVHD Series Single Panel Rigging Bar

EVH270 - EVHD Series Rear Support Bracket (Quick Rig Version)

EVH286 - EVHD Series 8 Panel Transport Case

EVH302 - EVHD Series Rigging Bar Support Feet (Stacking Bar)

EVH484 - EVHD Series Ground Stack Clamp

EVHD3™

SKU# EVH339

The EVHD3™ is a 3.9mm pixel pitch black face LED display. It's light weight durable die-cast aluminum frame and modular front maintenance design, allows for easy installation and service. Features include a seamless bezel-free design, no fan metal cooling structure, and excellent color uniformity and brightness. The EVHD3™ is ideal for any broadcast installations.

