

VOLT+ BAR S



6x 20W RGBMA+UV LED Battery Bar

PRELIMINARY DATA SHEET



KEY FEATURES

- (6) 20W RGBLA+UV LED Array
- 5020 Total Fixture Lumen Output (Sphere)
- 90.9 CRI
- Battery or AC Operation
- Extra Large 50mm Lenses
- Beam Angle: 30°x 14° (Frost Filter Included)
- Full Pixel Control
- Integrated L Track for Flexible Mounting
- Unique End-to-End Interconnection System
- >12hr Maximum Battery Run Time
- IP65 Rated

The **VOLT+ BAR S** is the next evolution in creative LED batten solutions, now featuring a high-performance battery system for ultimate flexibility. Combining the latest in LED color technology with the freedom of wireless operation, this fixture empowers designers to push creative boundaries without the constraints of power cables.

Building on the success of Elation's **SIX+ BAR S** and **L**, the **VOLT+ BAR S** offers the same high output, expanded color spectrum, and a superior quality of light. Equipped with powerful 20W RGB+Lime+Amber+UV LEDs and boasting an impressive CRI of 90.9, this fixture delivers stunning, high-fidelity color rendering with beautifully homogenized output. Its advanced optical system ensures even light distribution, while the proprietary RGBLA+UV engine produces exceptional whites and vibrant primaries with no color fringing. The extra-large 50 mm lenses make it ideal for direct view applications, while individual cell control opens up a world of design possibilities.

Designed for true mobility, the **VOLT+ BAR S** features an integrated high-capacity battery for untethered operation in any environment. Whether it's used in a temporary outdoor setup, a fast-paced production, or an installation where power access is limited, the battery system ensures hours of reliable performance. A built-in battery management system optimizes power usage, while multiple charging options make recharging simple and efficient.

Measuring half a meter in length, the **VOLT+ BAR S** houses six RGBLA+UV LEDs and delivers over 5020 lumens of output. It features fully variable color temperature adjustment (2400K - 8500K), CMY emulation, and a virtual gel library for seamless color customization. The integrated accessory slot accommodates the included frost filter, with optional ND filters and other optics available. The fixture also ships with a glare shield for wall wash applications.

For maximum versatility, the **VOLT+ BAR S**'s innovative housing allows for end-to-end interconnection and includes an integrated L track on three sides for flexible mounting and positioning. Adjustable trunnions can be fixed at multiple points, allowing optimal placement around objects or obstacles.

Encased in a rugged, fully IP65-rated housing, the **VOLT+ BAR S** is built to withstand any environment—indoors or outdoors. A durable C4-M marine-grade coating protects against harsh conditions, including salty coastal air, while fanless convection cooling ensures silent operation, making it ideal for noise-sensitive settings.

With wired and wireless control options—including DMX/RDM, IR Remote, Prebuilt & Custom Standalone Effect Sequences, proprietary Aria x2 wireless device management and NFC Configuration—the **VOLT+ BAR S** delivers seamless system integration and effortless control.

Break free from power limitations and set your creativity in motion with the **VOLT+ BAR S**!



Specifications are subject to change without notice ©Elation Professional 08/01/2025
Elation Professional USA | 6122 S. Eastern Ave. | Los Angeles, CA. 90040
323-582-3322 | 323-832-9142 fax | www.elationlighting.com | info@elationlighting.com

Elation Professional B.V. | Junostraat 2 | 6468 EW Kerkrade, The Netherlands
+31 45 546 85 66 | +31 45 546 85 96 fax | www.elationlighting.eu | info@elationlighting.eu

VOLT+ BAR S



6x 20W RGBMA+UV LED Battery Bar

SPECIFICATIONS

SOURCE

(6) x 20W RGBLA+ UV LEDs
30,000 Hour Average LED Life*

*May vary depending on several factors including but not limited to:
Environmental Conditions, Power/Voltage, Usage Patterns (On-Off
Cycling), Control and Dimming.

PHOTOMETRIC DATA

Total Lumen Output:
5,020 (Integrating Sphere)
CRI- 90.9
TLCI- 80

No Lens

Beam Angle: 20°
Field Angle: 33°

Included Frost

Beam Angle: 30°
Field Angle: 60°

EFFECTS

Prebuilt & Custom Standalone Effect Sequences
Full Pixel Control
Electronic Dimmer and Strobe
Variable 16-bit Dimming Modes and Curves

COLOR

RGBLA+ UV Color Array
CMY Emulation
Variable CCT 2400K - 8500K
Virtual Gel Swatch Book

CONTROL / CONNECTIONS

13 DMX Channel Modes (1ch, 3ch, 6ch, 9ch, 14ch,
17ch, 17ch, 23ch, 23ch, 35ch, 47ch, 83ch, 36ch)
4 Button Control Panel, LED Display
Aria x2 Wireless Device Management
IR Remote
NFC Configuration
RDM (Remote Device Management)
IP65 5pin XLR DMX In/Out
IP65 Locking Power Cable In/Out

SIZE / WEIGHT

Length: 19.7" (500mm)
Width: 6.9" (176mm)
Vertical Height: 8.9" (227mm)
Weight: 18.8 lbs / 8.55kg

ELECTRICAL / THERMAL

AC 100-240V - 50/60Hz
110W Max Power Consumption
Power Thru Capacity: 10A (10 units @110V; 21 units
@240V)
5°F to 113°F (-15°C to 45°C)
BTU/hr (+/- 10%) 375.1

BATTERY

Lithium Ion Rechargeable
Battery Capacity: 10.2 Ah
Battery Voltage: 18.5
Charge Time: 3hr
Battery Life: >12hr
Battery Recharge Cycles: >300 to 80% Capacity

INCLUDED ITEMS

Safety Cable
IP65 Locking Power Cable
Frost Filter
Glare Shield
Fixture Interconnect Splice

OPTIONAL ITEMS

6 Unit Charging Case
BAR S NSP Lens (BLS021)
BAR S WFL Lens (BLS061)
BAR S XFL Lens (BLS101)
BAR S L140 Lens (BLS141)
BAR S L1060 Lens (BLS161)
BAR S Dome Frost Lens (BLS181)
BAR S Black Lens (BLS125)
8050000053 - Omega Bracket (Qty.2)
Fixture Interconnect Splice Package (FISP06)
L-Track to M10 Adapter, 70mm (LTR001)
L-Track to M10 Adapter, 44.5mm (LTR008)
L Track C-Clamp & Adapter Assembly, 70mm (LTR100)
L Track C-Clamp & Adapter Assembly, 44.5mm (LTR112)
Interconnect Clamp Adapter (FICA01)

APPROVALS / RATINGS

CE | cETLus | IP65 | FCC | UKCA



Specifications are subject to change without notice ©Elation Professional 08/01/2025
Elation Professional USA | 6122 S. Eastern Ave. | Los Angeles, CA. 90040
323-582-3322 | 323-832-9142 fax | www.elationlighting.com | info@elationlighting.com


Elation Professional B.V. | Junostraat 2 | 6468 EW Kerkrade, The Netherlands
+31 45 546 85 66 | +31 45 546 85 96 fax | www.elationlighting.eu | info@elationlighting.eu

VOLT+ BAR S



6x 20W RGBMA+UV LED Battery Bar

UNIT DIMENSIONS



ORDERING INFORMATION

VOL405	1237000393	VOLT+ BAR S
--------	------------	-------------



Specifications are subject to change without notice ©Elation Professional 08/01/2025
Elation Professional USA | 6122 S. Eastern Ave. | Los Angeles, CA. 90040
323-582-3322 | 323-832-9142 fax | www.elationlighting.com | info@elationlighting.com

Elation Professional B.V. | Junostraat 2 | 6468 EW Kerkrade, The Netherlands
+31 45 546 85 66 | +31 45 546 85 96 fax | www.elationlighting.eu | info@elationlighting.eu