





4x60W IP65 RGBL Wash Fixture

PRELIMINARY DATA SHEET



KEY FEATURES

IP65 for temporary outdoor applications

(4) 60W RGBL LED Array

Up to 4000 Total Lumens Fixture Output

Pixel Control

Calibrated Color Temperature Control

Wide Zoom Range from 5° to 40°

The **REBEL WASH 4**™ is a powerful IP65-rated LED wash for many interior and exterior applications.

Projecting up to 4000 lumens output from4 60W RGBL emitters, the **REBEL WASH 4**™ is the ideal work horse luminare providing high output with powerful beams or wide washes, with excellent color quality. From intense primary colors to excellent white color quality with high CRI and calibrated color temperatures, the fixture is the perfect choice for a wide variety of applications. Pixel control or simple uniform access provide additional levels of excitement and effects, and the 360 degree endless Pan and Tilt rotation allows the fixture add another layer of creativity.

With a fast zoom range from 5° to 40° out of a compact fixture design, the **REBEL WASH 4**™ has the complete feature set for a wide variety of shows and events. Fully sealed from dust and water, it is a flexible fixture ready to perform in short-term outdoor applications or any indoor environment.



REBEL WASH 4





4x60W IP65 RGBL Wash Fixture

SPECIFICATIONS

SOURCE

(4) 60W RGBL LED 30,000 Hour Average LED Life*

*Test lab conditions. May vary depending on several factors including but not limited to: Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control, and Dimming.

PHOTOMETRIC DATA

4000 Total Lumen Fixture Output

CRI - 83.4 TLCI - 67

Zoom Range 5° - 40° Beam Angle: 5° - 40° Field Angle: 8.5° - 56.5°

EFFECTS

Motorized Zoom Pixel Control Variable 16-bit Dimming Curves

High Speed Electronic Shutter and Strobe

DMX Controllable LED Refresh Rate

Pan Angle: 540° Tilt Angle: 270°

Continuous 360° Pan and Tilt Rotation

COLOR

RGBL Color Array CMY Emulation Variable CCT 2400K - 8500K Virtual Gel Swatch Book

CONTROL / CONNECTIONS

3 DMX Channel Modes

DMX, RDM, Art-NET, sACN Protocol Support

(5) Button Touch Control Panel

Full Color 180° Reversible LCD Menu Display

Hibernation Mode (Power Save) IP65 Locking 5pin XLR Connector In/Out

IP65 Locking RJ45 Ethernet Connector In/Out

IP65 Locking Power Connector In/Thru

SIZE / WEIGHT

Legth: 11.7 in (298 mm)

Width: 8.1 in (205 mm) Height: 14.2 in (360 mm) Weight: 19 lbs. (8.6 kg)

ELECTRICAL

AC 100-240V 50/60Hz Max Power Consumption 340W -4° to 113°F (-20°C to 45°C)

INCLUDED ITEMS


Omega Brackets (x2) Safety Cable IP65 Rated Locking Power Cable

APPROVALS / RATINGS CE | cETLus | FCC | UKCA | IP65





ORDERING INFORMATION







REBEL WASH 4





4x60W IP65 RGBL Wash Fixture

DIMENSIONS

