



KEY FEATURES

IP65 for temporary outdoor applications

(4) 60W RGBL LED Array

Up to 4000 Total Lumens Fixture Output

Pixel Control

Calibrated Color Temperature Control

Wide Zoom Range from 5° to 40°

The **REBEL WASH 4™** is a powerful IP65-rated LED wash for many interior and exterior applications.

Projecting up to 4000 lumens output from 4 60W RGBL emitters, the **REBEL WASH 4™** is the ideal work horse luminaire providing high output with powerful beams or wide washes, with excellent color quality. From intense primary colors to excellent white color quality with high CRI and calibrated color temperatures, the fixture is the perfect choice for a wide variety of applications. Pixel control or simple uniform access provide additional levels of excitement and effects, and the 360 degree endless Pan and Tilt rotation allows the fixture add another layer of creativity.

With a fast zoom range from 5° to 40° out of a compact fixture design, the **REBEL WASH 4™** has the complete feature set for a wide variety of shows and events. Fully sealed from dust and water, it is a flexible fixture ready to perform in short-term outdoor applications or any indoor environment.

REBEL™ WASH 4



4x60W IP65 RGBL Wash Fixture

SPECIFICATIONS

SOURCE

(4) 60W RGBL LED
30,000 Hour Average LED Life*
*Test lab conditions. May vary depending on several factors including but not limited to: Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control, and Dimming.

PHOTOMETRIC DATA

4000 Total Lumen Fixture Output
CRI - 83.4
TLCI - 67
Zoom Range 5° - 40°
Beam Angle: 5° - 40°
Field Angle: 8.5° - 56.5°

EFFECTS

Motorized Zoom
Pixel Control
Variable 16-bit Dimming Curves
High Speed Electronic Shutter and Strobe
DMX Controllable LED Refresh Rate
Pan Angle: 360/540°
Tilt Angle: 360/270°
Continuous 360° Pan and Tilt Rotation

COLOR

RGBL Color Array
Variable CCT 2400K - 8500K
Virtual Gel Swatch Book

CONTROL / CONNECTIONS

3 DMX Channel Modes
DMX, RDM, Art-NET, sACN Protocol Support
(4) Button Touch Control Panel
Full Color 180° Reversible LCD Menu Display
Hibernation Mode (Power Save)
Aria x2 Wireless Device Management
NFC Configuration
IP65 Locking 5pin XLR Connector In/Out
IP65 Locking RJ45 Ethernet Connector In/Out
IP65 Locking Power Connector In/Thru

SIZE / WEIGHT

Length: 11.7 in (298 mm)
Width: 8.1 in (205 mm)
Height: 14.2 in (360 mm)
Weight: 19 lbs. (8.6 kg)

ELECTRICAL

AC 100-240V 50/60Hz
Max Power Consumption 340W
Power Thru Capacity: 8A (2 units @115V, 5 units @240V)
-4° to 113°F (-20°C to 45°C)
BTU/hr (+/- 10%) 1159.4

INCLUDED ITEMS

Omega Brackets (x2)
Safety Cable
IP65 Rated Locking Power Cable

APPROVALS / RATINGS

CE | cETLus | FCC | UKCA | IP65



ORDERING INFORMATION

SKU (US)	SKU (EU)	DESCRIPTION
REB104	1237000394	Elation Rebel Wash 4



Specifications are subject to change without notice ©Elation Professional 03/17/2026
Elation Professional USA | 6122 S. Eastern Ave. | Los Angeles, CA. 90040
323-582-3322 | 323-832-9142 fax | www.elationlighting.com | info@elationlighting.com

Elation Professional B.V. | Junostraat 2 | 6468 EW Kerkrade, The Netherlands
+31 45 546 85 66 | +31 45 546 85 96 fax | www.elationlighting.eu | info@elationlighting.eu



4x60W IP65 RGBL Wash Fixture

DIMENSIONS

