

**KEY FEATURES**

- IP65 for temporary outdoor applications
- (12) 60W RGBW LED Array
- Up to 14000 Total Lumens Fixture Output
- Pixel Control
- Calibrated Color Temperature Control
- Wide Zoom Range from 5° to 40°
- 360° continuous Pan and Tilt

The **REBEL WASH 12™** is a powerful IP65-rated LED wash for many interior and exterior applications.

Projecting up to 14000 lumens output from 12 60W RGBW emitters, the **REBEL WASH 12™** is the ideal work horse luminare providing high output with powerful beams or wide washes, with excellent color quality. From intense primary colors to excellent white color quality with high CRI and calibrated color temperatures, the fixture is the perfect choice for a wide variety of applications. Pixel control or simple uniform access provide additional levels of excitement and effects, and the 360 degree endless Pan and Tilt rotation allows the fixture add another layer of creativity.

With a fast zoom range from 5° to 40° out of a compact fixture design, the **REBEL WASH 12™** has the complete feature set for a wide variety of shows and events. Fully sealed from dust and water, it is a flexible fixture ready to perform in short-term outdoor applications or any indoor environment.



12x60W IP65 RGBL Wash Fixture

SPECIFICATIONS

SOURCE

(12) 60W RGBL LED
30,000 Hour Average LED Life*

*Test lab conditions. May vary depending on several factors including but not limited to: Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control, and Dimming.

PHOTOMETRIC DATA

14000 Total Lumen Fixture Output
CRI - 83.4
TLCI - 67
Zoom Range 5° - 40°
Beam Angle: 5° - 40°
Field Angle: 8.5° - 56.5°

EFFECTS

Motorized Zoom
Pixel Control
Variable 16-bit Dimming Curves
High Speed Electronic Shutter and Strobe
DMX Controllable LED Refresh Rate
Pan Angle: 360/540°
Tilt Angle: 360/270°
Continuous 360° Pan and Tilt Rotation

COLOR

RGBL Color Array
CMY Emulation
Variable CCT 2400K - 8500K
Virtual Gel Swatch Book

CONTROL / CONNECTIONS

3 DMX Channel Modes (21/28/68)
DMX, RDM, Art-NET, sACN Protocol Support
(5) Button Touch Control Panel
Full Color 180° Reversible LCD Menu Display
Hibernation Mode (Power Save)
IP65 Locking 5pin XLR Connector In/Out
IP65 Locking RJ45 Ethernet Connector In/Out
IP65 Locking Power Connector In

SIZE / WEIGHT

Length: 14.2 in (360 mm)
Width: 10.2 in (259 mm)
Height: 17.5 in (445 mm)
Weight: 36.1 lbs. (16.35 kg)

ELECTRICAL

AC 100-240V 50/60Hz
Max Power Consumption 700W
-4° to 113°F (-20°C to 45°C)

INCLUDED ITEMS

Omega Brackets (x2)
Safety Cable
IP65 Rated Locking Power Cable

APPROVALS / RATINGS

CE | cETLus | FCC | UKCA | IP65



ORDERING INFORMATION

SKU (US)	SKU (EU)	DESCRIPTION
REB112	1237000395	Elation Rebel Wash 12





12x60W IP65 RGBW Wash Fixture

UNIT DIMENSIONS

