



8x60W IP65 RGBL Wash Fixture

PRELIMINARY DATA SHEET



KEY FEATURES

(8) 60W RGBL LEDs with Pixel Control

(16) 5W CW Sparx LEDs with Pixel Control

11,548 Total Fixture Lumen Output (Sphere)

4° - 35° Beam Angle

Fast and precise 210° Tilt Rotation

IP55 Tilt FX Fixture

The **REBEL LINE 8** defies expectations for linear lighting in a compact 8-cell format, delivering impressive output, precision, and color consistency in a versatile IP55 design. Its eight high-intensity 60W RGBL engines and sixteen CW SparkX pixels ignite the stage with 11,548 lumens of relentless, full-spectrum brilliance.

A seamless linear lens system and rapid 210° tilt movement create bold, continuous beams that transform effortlessly from razor-sharp aeriels to a smooth, enveloping wash. The integrated Sparkle Beam FX adds refined texture, while the SparkX cool-white crossing beams cut through the scene with crisp, unmistakable definition.

A built-in magnetic alignment system allows the **REBEL LINE 8** to snap together with other LINE fixtures, forming flawless beam lines and high-impact pixel effects that read as one continuous visual element across any stage. Paired with its rugged IP65 construction and compact, tour-ready form, the **REBEL LINE 8** is built for environments demanding bold intensity, sweeping kinetic motion, and advanced pixel artistry for any stage.



8x60W IP65 RGBL Wash Fixture

SPECIFICATIONS

SOURCE

- (8) 60W RGBL LEDs
- (16) 5W CW SparkX LED Pixels
- 30,000 Hour Average LED Life*

*Test lab conditions. May vary depending on several factors including but not limited to:

Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control, and Dimming.

PHOTOMETRIC DATA

- Total Lumen Output:
- Integrating Sphere
- All LED: 11,548 Lumens
- RGBL LED: 7,128 Lumens
- CW LED: 4,752 Lumens
- CRI 82
- Zoom Range 4° - 35°

EFFECTS

- Motorized Zoom
- Full Pixel LED Control
- SparkX LED Beam Effect
- Electronic Dimmer and Strobe
- Variable 16-bit Dimming Modes and Curves
- Tilt Angle: 210°

COLOR

- RGBL LED Array
- CW SparkX LED Array
- Variable CCT 2400K - 8500K
- Virtual Gel Swatch Book

CONTROL / CONNECTIONS

- 3 DMX Channel Modes (22/30/70 channels)
- DMX Adjustable Refresh Rate (900 -25000 Hz)
- 4 Button Control Panel, LED Display
- Aria x2 Wireless Device Management
- NFC Configuration
- DMX, RDM, Art-NET, sACN Protocol Support
- IP65 Locking 5pin XLR Connector In/Out
- IP65 Locking RJ45 Ethernet Connector In/Out
- IP65 Locking Power Cable In/Out

SIZE / WEIGHT

- Length: 19.7 in (500mm)
- Width: 6.1 in (168mm)
- Height (head up): 13.4 in (342mm)
- Height (head 90 degree): 10 in (254mm)
- Weight: 29 lb (13.2 kg)

ELECTRICAL / THERMAL

- AC 100-240V 50/60Hz
- 810W Max Power Consumption
- Ambient Temperature Range: -4°F to 113°F (-20°C to 45°C)
- BTU/hr (+/- 10%) 2762.1

INCLUDED ITEMS

- Omega Brackets (x2)
- Blank Name Plate
- Front Louver/Grid
- Diffusion Filter
- Safety Cable IP65 Rated
- IP65 Locking Power Cable

APPROVALS / RATINGS

IP55

ORDERING INFORMATION

SKU (US)	SKU (EU)	DESCRIPTION
REB208	111787	Elation Rebel Line 8





8x60W IP65 RGLB Wash Fixture

UNIT DIMENSIONS

