



## KEY FEATURES

- (8) 60W RGBL LEDs with Pixel Control
- (16) 5W CW Sparx LEDs with Pixel Control
- 11,548 Total Fixture Lumen Output (Sphere)
- 4° - 35° Beam Angle
- Fast and precise 210° Tilt Rotation
- IP65 Tilt FX Fixture

The **REBEL LINE 8™** is a dynamic IP65-rated LED tilt FX fixture for diverse interior and exterior applications. Projecting up to 11,548 lumens output from (8) 60W RGBL LEDs and (16) 5W CW SparkX LEDs—all with individual pixel control—the **REBEL LINE 8™** is the ideal versatile luminaire delivering high output with focused beams or expansive washes, complemented by superior color quality. From vivid primary hues and seamless RGBL blending to crisp white light with high CRI and tunable temperatures from the CW SparkX array, the fixture excels across a broad spectrum of creative uses. Pixel-by-pixel control or unified output modes unlock layers of dynamic effects and patterns, while the fast and precise 210° tilt rotation adds fluid motion and aerial creativity. With a versatile beam angle from 4° to 35° in a streamlined fixture design, the **REBEL LINE 8™** offers a comprehensive feature set for immersive shows, events, and installations. Fully sealed against dust and water, it stands ready for temporary outdoor deployments or any indoor setting.



8x60W IP65 RGBL Wash Fixture

## SPECIFICATIONS

### SOURCE

(8) 60W RGBL LEDs  
(16) 5W CW Sparx LED Pixels  
30,000 Hour Average LED Life\*

\*Test lab conditions. May vary depending on several factors including but not limited to: Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control, and Dimming.

### PHOTOMETRIC DATA

Total Lumen Output:  
Integrating Sphere  
All LED: 11,548 Lumens  
RGBL LED: 7,128 Lumens  
CW LED: 4,752 Lumens  
CRI 82  
Zoom Range 4° - 35°

### EFFECTS

Motorized Zoom  
Full Pixel LED Control  
Sparx LED Beam Effect  
Electronic Dimmer and Strobe  
Variable 16-bit Dimming Modes and Curves  
Tilt Angle: 210°

### COLOR

RGBL LED Array  
CW Sparx LED Array  
Variable CCT 2400K - 8500K  
Virtual Gel Swatch Book

### CONTROL / CONNECTIONS

3 DMX Channel Modes (22/30/70 channels)  
DMX Adjustable Refresh Rate (900 - 25000 Hz)  
4 Button Control Panel, LED Display  
Aria x2 Wireless Device Management  
NFC Configuration  
DMX, RDM, Art-NET, sACN Protocol Support  
IP65 Locking 5pin XLR Connector In/Out  
IP65 Locking RJ45 Ethernet Connector In/Out  
IP65 Locking Power Cable In/Out

### SIZE / WEIGHT

Length: 19.8 in (502mm)  
Width: 6.1 in (168mm)  
Height (head up): 13.4 in (342mm)  
Height (head 90 degree): 10 in (254mm)  
Weight: TBD

### ELECTRICAL / THERMAL

AC 100-240V 50/60Hz  
700W Max Power Consumption  
Ambient Temperature Range: -4°F to 113°F  
(-20°C to 45°C)  
BTU/hr (+/- 10%) 2384

### INCLUDED ITEMS

Omega Brackets (x2)  
Front Louver/Grid  
Safety Cable IP65 Rated  
IP65 Locking Power Cable

### APPROVALS / RATINGS

IP65

## ORDERING INFORMATION

SKU (US)	SKU (EU)	DESCRIPTION
REB208	111787	Elation Rebel Line 8





8x60W IP65 RGBL Wash Fixture

## UNIT DIMENSIONS

