

# REBEL™ LINE 16



IP65 16x RGBL Dual Head Tilt FX Bar

**PRELIMINARY DATA SHEET**

## KEY FEATURES

- (16) 60W RGBL LEDs with Pixel Control
- (32) 5W CW SparkX LEDs with Pixel Control
- 25,355 Total Fixture Lumen Output (Sphere)
- 4° - 35° Beam Angle
- Fast and precise 210° Tilt Rotation
- IP55 Tilt FX Fixture



The **REBEL LINE 16** amplifies the force of the Rebel Series with a commanding 16-cell format—delivering massive output, precision optics, and a rich, full-spectrum palette inside a rugged IP55 chassis. Sixteen high-intensity 60W RGBL engines and thirty-two CW SparkX pixels surge together to unleash 25,355 lumens of relentless color and cool-white punch for designers who push their rigs harder.

A seamless linear lensing system and fast 210° tilt movement drive dynamic, fluid looks—ranging from razor-sharp sub-4° beams that cut through the air to immersive 35°+ washes that fill a stage with ease. With integrated SparkX, the **REBEL LINE 16** adds dimensional texture and atmospheric detail, its cool-white crossing beams carving crisp, unmistakable lines through the haze.

A built-in magnetic alignment system allows the **REBEL LINE 16** to lock effortlessly with other LINE fixtures—including the LINE 8—forming continuous beams and high-resolution pixel arrays at any scale. With its tour-ready build and expansive pixel density, the **REBEL LINE 16** is engineered for productions that demand bold intensity, sweeping kinetic motion, and advanced pixel artistry built to command the biggest stages.



# REBEL™ LINE 16



IP65 16x RGBL Dual Head Tilt FX Bar

## SPECIFICATIONS

### SOURCE

(16) 60W RGBL LEDs  
(32) 5W CW SparkX LED Pixels  
30,000 Hour Average LED Life\*

\*Test lab conditions. May vary depending on several factors including but not limited to: Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control, and Dimming.

### PHOTOMETRIC DATA

Total Lumen Output:  
Integrating Sphere  
All LED: 25,355 Lumens  
RGBL LED: 13,865 Lumens  
CW LED: 11,546 Lumens  
CRI 82  
Zoom Range 4° - 35°

### EFFECTS

Motorized Zoom  
Full Pixel LED Control  
SparkX LED Beam Effect  
Electronic Dimmer and Strobe  
Variable 16-bit Dimming Modes and Curves  
Tilt Angle: 210°

### COLOR

RGBL LED Array  
CW SparkX LED Array  
Variable CCT 2400K - 8500K  
Virtual Gel Swatch Book

### CONTROL / CONNECTIONS

6 DMX Channel Modes (24, 31, 122, 2x 22, 2x 30 & 2x 70 channels)  
DMX Adjustable Refresh Rate (900 - 25000 Hz)  
4 Button Control Panel, LED Display  
Aria x2 Wireless Device Management  
NFC Configuration  
DMX, RDM, Art-NET, sACN Protocol Support  
IP65 Locking 5pin XLR Connector In/Out  
IP65 Locking RJ45 Ethernet Connector In/Out  
IP65 Locking Power Cable In/Out

### SIZE / WEIGHT

Length: 39.4 in (1000mm)  
Width: 6.1 in (168mm)  
Height (head up): 13.4 in (342mm)  
Height (head 90 degree): 10 in (254mm)  
Weight: 55 lb (24.9 kg)

### ELECTRICAL / THERMAL

AC 100-240V 50/60Hz  
1690W Max Power Consumption  
Ambient Temperature Range: -4°F to 113°F  
(-20°C to 45°C)  
BTU/hr (+/- 10%) 5,762.9

### INCLUDED ITEMS

Omega Brackets (x2)  
Blank Name Plate  
Front Louver/Grid (x2)  
Diffusion Filter (x2)  
Safety Cable IP65 Rated  
IP65 Locking Power Cable

### APPROVALS / RATINGS

IP55



## ORDERING INFORMATION

US SKU	EU SKU	DESCRIPTION
REB216	PENDING	Elation Rebel Line 16



