



BATTEN 12

4x100W RGBMA LEDs IP65 Light Engine



ELATION®

PRELIMINARY DATA SHEET



KEY FEATURES

- (4) 100W RGBMA LED Array
- 10,981 Total Fixture Lumen Output (Sphere)
- Full Pixel Control
- Integrated Lens and Accessory Slots
- Art-Net & sACN Support
- Integrated L Track for Flexible Mounting
- End-to-End Magnetic Alignment System
- NFC & Aria x2 Wireless Device Management
- IP65 Rated

Delivering rich, full-spectrum color and over 10,500 lumens of output, the **KL BATTEN 12** brings natural, full-spectrum light to stages, studios, and the outdoors—all in a compact, durable design.

Built for designers who demand professional color and powerful output, the **KL BATTEN 12** provides homogeneous, true-to-life color via RGBMA LED engine with high CRI that's natural on camera and on stage, producing a smooth, even field.

An IP-65 rating means it can be used nearly anywhere. Its quiet operation, intuitive control, and flexible mounting options make it a versatile, reliable, and colorful addition to any rig.



Specifications are subject to change without notice ©Elation Professional 12/19/2025

Elation Professional USA | 6122 S. Eastern Ave. | Los Angeles, CA. 90040
323-582-3322 | 323-832-9142 fax | www.elationlighting.com | info@elationlighting.com

Elation Professional B.V. | Junostraat 2 | 6468 EW Kerkrade, The Netherlands
+31 45 546 85 66 | +31 45 546 85 96 fax | www.elationlighting.eu | info@elationlighting.eu



BATTEN 12



ELATION®

4x100W RGBMA LEDs IP65 Light Engine

SPECIFICATIONS

SOURCE

(4) x 100W RGBMA LEDs

30,000 Hour Average LED Life*

*May vary depending on several factors including but not limited to: Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control and Dimming.

PHOTOMETRIC DATA

Total Lumen Output:

10,981 (Integrating Sphere)

CRI- 94.9

TLCI- 95

Beam Angle: 22° x 20°

Field Angle: 44° x 42°

EFFECTS

Full Pixel Control

Electronic Dimmer and Strobe

Variable 16-bit Dimming Modes and Curves

COLOR

RGBMA Color Array

CMY Emulation

16bit Fully Variable CCT 2400K - 8500K

Green/Magenta Shift

Dim-to-Warm Fade

Virtual Gel Swatch Book

CONTROL / CONNECTIONS

22 DMX Channel Modes (1ch, 3ch, 4ch-A, 4ch-B, 4ch-C, 9ch, 10ch, 14ch, 22ch, 16ch, 6ch, 8ch-A, 8ch-B, 20ch-A, 20ch-B, 32ch, 12ch, 16ch-A, 16ch-B, 40ch, 32ch, 54ch)

4 Button Control Panel, Color LED Display

RDM (Remote Device Management)

Aria x2 Wireless Device Management

NFC Configuration

IP65 5pin XLR DMX In/Out

IP65 RJ45 Ethernet In/Out (Art-Net & sACN)

IP65 Locking Power Cable In/Out

SIZE / WEIGHT

Length: 5.8" (148mm)

Width: 12.6" (321mm)

Vertical Height: 8.5" (216mm)

Weight: 14.7 lbs / 6.65kg

ELECTRICAL / THERMAL

AC 100-240V - 50/60Hz

200W Max Power Consumption

Power Thru Capacity: 11A (6 units @110V; 13 units @240V)

5°F to 113°F (-15°C to 45°C)

BTU/hr (+/- 10%) 682

INCLUDED ITEMS

Glare Shield

Border Light Filter

Safety Cable

IP65 Locking Power Cable

OPTIONAL ITEMS

90deg Slotted Omega Bracket (OB-107-90B)

(Qty.1)

L-Track to M10 Adapter, 70mm (LTR001)

L-Track to M10 Adapter, 44.5mm (LTR008)

L Track C-Clamp & Adapter Assembly, 70mm (LTR100)

L Track C-Clamp & Adapter Assembly, 44.5mm (LTR112)



Specifications are subject to change without notice ©Elation Professional 12/19/2025

Elation Professional USA | 6122 S. Eastern Ave. | Los Angeles, CA. 90040
323-582-3322 | 323-832-9142 fax | www.elationlighting.com | info@elationlighting.com

Elation Professional B.V. | Junostraat 2 | 6468 EW Kerkrade, The Netherlands
+31 45 546 85 66 | +31 45 546 85 96 fax | www.elationlighting.eu | info@elationlighting.eu







BATTEN 12

4x100W RGBMA LEDs IP65 Light Engine



ELATION[®]

UNIT DIMENSIONS



ORDERING INFORMATION

SKU (US)	SKU (EU)	DESCRIPTION
KLB112	N/A	KL Batten 12



Specifications are subject to change without notice ©Elation Professional 12/19/2025

Elation Professional USA | 6122 S. Eastern Ave. | Los Angeles, CA. 90040
323-582-3322 | 323-832-9142 fax | www.elationlighting.com | info@elationlighting.com

Elation Professional B.V. | Junostraat 2 | 6468 EW Kerkrade, The Netherlands
+31 45 546 85 66 | +31 45 546 85 96 fax | www.elationlighting.eu | info@elationlighting.eu