



BATTEN 72

24x100W RGBMA LEDs IP65 Light Engine



ELATION®

PRELIMINARY DATA SHEET



KEY FEATURES

- (24) 100W RGBMA LED Array
- 71,347 Total Fixture Lumen Output (Sphere)
- Full Pixel Control
- Integrated Lens and Accessory Slots
- Art-Net & sACN Support
- Integrated L Track for Flexible Mounting
- End-to-End Magnetic Alignment System
- NFC & Aria x2 Wireless Device Management
- IP65 Rated

The **KL Batten 72** is built for stages and studios that demand rich, full-spectrum color and commanding output.

Its advanced RGBMA engine delivers smooth, natural light that blends cleanly across scenery. At the same time, more than 30,000 lumens provide confident, room-filling coverage for large cycs, wide sets, and high-impact scenic looks.

A weather-ready housing and integrated L-Track system make installation easy indoors or out, and its advanced control options ensure reliable performance—from subtle color shifts to complex pixel-mapped effects.

For designers who rely on both power and precision, the **KL Batten 72** delivers the bold, consistent results that anchor any professional lighting design.



Specifications are subject to change without notice ©Elation Professional 12/18/2025

Elation Professional USA | 6122 S. Eastern Ave. | Los Angeles, CA. 90040
323-582-3322 | 323-832-9142 fax | www.elationlighting.com | info@elationlighting.com

Elation Professional B.V. | Junostraat 2 | 6468 EW Kerkrade, The Netherlands
+31 45 546 85 66 | +31 45 546 85 96 fax | www.elationlighting.eu | info@elationlighting.eu



BATTEN 72



ELATION®

24x100W RGBMA LEDs IP65 Light Engine

SPECIFICATIONS

SOURCE

(24) x 100W RGBLA+ UV LEDs
30,000 Hour Average LED Life*

*May vary depending on several factors including but not limited to: Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control and Dimming.

PHOTOMETRIC DATA

Total Lumen Output:
71,347 (Integrating Sphere)
CRI- 94.9
TLCI- 95
Beam Angle: 82° x 22°
Field Angle: 97° x 53°

EFFECTS

Full Pixel Control
Electronic Dimmer and Strobe
Variable 16-bit Dimming Modes and Curves

COLOR

RGBMA Color Array
CMY Emulation
16bit Fully Variable CCT 2400K - 8500K
Green/Magenta Shift
Dim-to-Warm Fade
Virtual Gel Swatch Book

CONTROL / CONNECTIONS

52 DMX Channel Modes (1ch, 3ch, 4ch-A, 4ch-B, 4ch-C, 9ch, 10ch, 14ch, 22ch, 16ch, 6ch, 8ch-A, 8ch-B, 20ch-A, 20ch-B, 32ch, 12ch, 16ch-A, 16ch-B, 40ch, 32ch, 54ch, 24ch, 32ch-A, 32ch-B, 80ch, 56ch, 96ch, 36ch, 48ch-A, 48ch-B, 120ch, 80ch, 142, 72ch, 96ch-A, 96ch-B, 240ch, 152ch, 174ch)
4 Button Control Panel, Color LED Display
RDM (Remote Device Management)
Aria x2 Wireless Device Management
NFC Configuration
IP65 5pin XLR DMX In/Out
IP65 RJ45 Ethernet In/Out (Art-Net & sACN)
IP65 Locking Power Cable In

SIZE / WEIGHT

Length: 5.8" (148mm)
Width: 71.1" (148mm)
Vertical Height: 8.5" (217mm)
Weight: 60.4 lbs / 27.4kg

ELECTRICAL / THERMAL

AC 100-240V - 50/60Hz
1200W Max Power Consumption
5°F to 113°F (-15°C to 45°C)
BTU/hr (+/- 10%) 4,092

INCLUDED ITEMS

Safety Cable
IP65 Locking Power Cable

OPTIONAL ITEMS

Omega Bracket (Qty.2)
L-Track to M10 Adapter, 70mm (LTR001)
L-Track to M10 Adapter, 44.5mm (LTR008)
L Track C-Clamp & Adapter Assembly, 70mm (LTR100)
L Track C-Clamp & Adapter Assembly, 44.5mm (LTR112)





BATTEN 72

24x100W RGBMA LEDs IP65 Light Engine




ELATION

ORDERING INFORMATION

SKU (US)	SKU (EU)	DESCRIPTION
KLB112	N/A	KL Batten 72

UNIT DIMENSIONS



ELATION

Specifications are subject to change without notice ©Elation Professional 12/18/2025

Elation Professional USA | 6122 S. Eastern Ave. | Los Angeles, CA. 90040
323-582-3322 | 323-832-9142 fax | www.elationlighting.com | info@elationlighting.com

Elation Professional B.V. | Junostraat 2 | 6468 EW Kerkrade, The Netherlands
+31 45 546 85 66 | +31 45 546 85 96 fax | www.elationlighting.eu | info@elationlighting.eu